

BLACK STAGE SLINGS

These lightweight roundslings are ideal for easy and inconspicuous suspension of stage sound and lighting equipment. Black sleeve material helps the sling blend into the surroundings. *Lift-All* stage slings include all of the *Tuflex*® features and benefits except that the color coding of the slings is achieved by using a color-coded identification tag. Double-wall sleeve material is standard.



Part Number	Color of Tags	Rated Capacity (lbs.)*			Min. Length (ft.)	Approximate Measurements			
		Vertical	Choker	Basket		Weight (lbs./ft.)	Body Dia. Relaxed (in.)	Contact Width (in.)	Min. Hardware Dia. (in.)
BSEN30	Purple	2,600	2,100	5,200	1-1/2	0.2	5/8	1-1/8	7/16
BSEN60	Green	5,300	4,200	10,600	1-1/2	0.3	7/8	1-1/2	5/8
BSEN90	Yellow	8,400	6,700	16,800	3	0.4	1-1/8	1-7/8	3/4



TUFLEX WIDE-LIFT

Wide Load Support and Balance

Tuflex Wide-Lift slings distribute the load over a wide area and offer better balance of larger loads, whether heavy or light.

Features and Benefits

Maintains all the basic *Tuflex* features plus...

Promotes Safety

- Wide body distributes load over wide area and offers improved stability.

Saves Money

- Bearing point of eyes can be shifted to prolong sling life.
- Custom sizes available to fit your needs.

Saves Time

- Standard eye length is 12", making hook-up easy and fast.
- Standard body width is 12", making load balancing easier.



Note:

Wide-lift slings should only be used in basket hitch.

Consult *Lift-All* for special requirements.

Code	Color of Eyes	Vertical Basket Hitch Rated Capacity* (lbs.)
WLEN30	Purple	5,200
WLEN60	Green	10,600
WLEN90	Yellow	16,800
WLEN120	Tan	21,200

* **WARNING** Do not exceed rated capacities. Sling tension increases as the angle from horizontal decreases. Slings should not be used at angles of less than 30°. Refer to the Effect of Angle chart in the General Information section of this catalog. **Always protect synthetic slings from being cut by corners and edges. See the Sling Protection section in this catalog.**