

DIRECT CONNECT HOOKS

Direct Connect hooks are the quickest and easiest way to add hooks to *Tuflex*® roundslings and web slings at your job site. No tools or extra parts are needed.

For *Tuflex* slings, just match the color-coded hook to the same color *Tuflex* sling, and you're ready to go. Rated capacities are the same for both the hook and the *Tuflex* roundslings.

Features and Benefits

- Rugged: The alloy steel hook and latch are forged for superior toughness.
- Color-coded hook matches *Tuflex* color and capacity.
- *Web-Trap*™ design keeps sling in place, ready to use.
- Four hook sizes to match *Tuflex* sizes EN30 (Purple), EN60 (Green), EN90 (Yellow) and EN150 (Red).
- Can be used with 1" and 2" web slings.
- Quick connections with no tools needed.
- Increases the life of the sling by reducing wear at the bearing point.

Part No.*	Color	Rated Capacity (lbs.)	Tuflex	Web Slings		A (in.)	B (in.)	C (in.)	D (in.)	E (in.)	F (in.)	G (in.)	H (in.)	I (in.)	J (in.)	K (in.)	Weight (lbs.)
				Width	Plies												
DCH1	Purple	2,600	EN30	1	1	3.38	1.56	0.91	4.84	0.47	0.81	.67	3.07	1.22	0.70	1.13	1.54
DCH2	Green	5,300	EN60	1	2	4.00	1.75	1.28	5.83	0.75	1.07	.83	3.58	1.57	0.88	1.39	2.65
DCH3	Yellow	8,400	EN90	2	1 & 2	4.63	2.13	1.40	6.89	0.83	1.26	.98	4.45	1.97	1.00	1.76	4.85
DCH4	Red	13,200	EN150	—	—	5.75	2.34	1.83	8.78	1.63	1.60	1.42	5.21	2.34	1.23	2.21	9.90

* Add an 'L' to end of part number to order replacement latch.

