

DYNAFLEX™ ROUNDSLING

Dyneema® High-Performance Core Ultra-Lightweight Roundsling

DynaFlex is manufactured with a load bearing core of *Dyneema*, the world's strongest fiber, yet remains soft and flexible to allow for easy rigging. This high capacity, ultra-lightweight roundsling is a safe and ergonomic alternative to steel and other forms of synthetic slings.



Features and Benefits



- **Ultra-Lightweight** – Approximately 20% lighter than *KeyFlex*™ and 52% lighter than *Tuflex*® for the same capacity, reducing the probabilities of hand and shoulder strains and sprains.
- **Good Chemical Resistance with Reduced Water Absorption** – A 10' *DynaFlex* sling will increase 6 pounds in water weight when rigged wet vs. 13 pounds for the same capacity and length *Tuflex* roundsling. Users will appreciate the weight reduction, minimizing rigger fatigue and increasing safety.
- **Neutral Buoyancy** – *DynaFlex* slings are a great choice for water recovery and lifting applications.
- **100% Dyneema Core (non-blended)** – We use the most advanced high tenacity fiber on the market for lifting slings. The homogeneous core fiber reacts uniformly regardless of lift application. Designed with your safety in mind.
- ***DynaFlex* Single Component Twisted Core** – Single path design allows higher strength retention around common rigging hardware. This saves time during hook up to the connection point and rigging vs. dual path slings. No need to worry about sling body orientation.
- **Promotes Safety** – Customized designs are available, including higher capacity and/or shorter length versions.

Note: *DynaFlex* slings are approved for use up to 158°F.

*  **WARNING**

Always protect roundslings from corners, edges, or protrusions. Refer to the Sling Protection section of this catalog to choose the right protection product for your lift.

DYNAFLEX™ ROUNDSLING



Item	Approximate Sling Weight (lbs.)	Vertical Capacity (lbs.)
DynaFlex Roundslings:		
DEN200K x 25-ft.	99	200,000
KeyFlex™ Roundslings:		
KEN200K x 25-ft.	130	200,000
KeyFlex Ultra Roundslings:		
KEN3P200 x 25-ft.	173	200,000
Tuflex® Roundslings (2 ea.):		
EN1000 x 25-ft.	207	180,000
Braided Tuflex Roundslings:		
B8E600 x 25-ft.	300	180,000
Wire Rope Sling (2 ea.):		
2-1/4" 6X37 IWRC x 25-ft.	669	176,000
Chain Sling (2 ea.):		
1-1/4" SOS x 25-ft.	870	144,600

DynaFlex Capacities and Measurements										
Part Number	Rated Capacity (lbs.)*				Min. Length (ft.)	Approximate Measurements				
	Vertical	Choker	Basket @ 90°	Basket @ 45°		Wt. (lbs per ft.)	Body Dia. Relaxed (in.)	Width @ Load (in.)	Minimum Hardware Diameter (in.)	Minimum Edge Contact Radii (in.)
DEN10K	10,000	8,000	20,000	14,100	2	0.25	1.00	1.56	0.69	0.23
DEN15K	15,000	12,000	30,000	21,000	3	0.38	1.13	1.75	0.88	0.31
DEN20K	20,000	16,000	40,000	28,000	3	0.44	1.25	2.00	1.06	0.37
DEN25K	25,000	20,000	50,000	35,000	3	0.54	1.25	2.13	1.25	0.47
DEN30K	30,000	24,000	60,000	42,000	3	0.66	1.38	2.13	1.44	0.50
DEN40K	40,000	32,000	80,000	56,000	3	0.79	1.75	2.75	1.50	0.53
DEN50K	50,000	40,000	100,000	70,000	5	1.16	1.88	2.88	1.75	0.62
DEN60K	60,000	48,000	120,000	84,000	5	1.31	2.00	3.13	2.00	0.69
DEN70K	70,000	56,000	140,000	98,000	8	1.47	2.13	3.25	2.19	0.76
DEN80K	80,000	64,000	160,000	113,000	8	1.59	2.25	3.50	2.38	0.82
DEN90K	90,000	72,000	180,000	127,000	8	1.94	2.50	3.88	2.38	0.83
DEN100K	100,000	80,000	200,000	141,000	8	2.06	2.75	4.25	2.50	0.84
DEN125K	125,000	100,000	250,000	176,000	8	2.60	3.00	4.88	2.63	0.92
DEN150K	150,000	120,000	300,000	210,000	8	3.24	3.25	5.25	2.88	1.00
DEN175K	175,000	140,000	350,000	240,000	8	3.51	3.50	5.75	3.13	1.10
DEN200K	200,000	160,000	400,000	280,000	8	3.90	3.75	6.13	3.38	1.18

* **WARNING** Always protect roundslings from corners, edges, or protrusions. Refer to the Sling Protection section of this catalog to choose the right protection product for your lift.