

POLYESTER STAGE SLINGS

These lightweight roundslings are ideal for easy and inconspicuous suspension of stage sound and lighting equipment. Black sleeve material helps sling blend into the surroundings. *Lift-All* stage slings include all of the *Tuflex*® features and benefits except that the color coding of the slings is achieved by using a color-coded identification tag. Double-wall sleeve material is standard.



Part Number	Color of Tags	Rated Capacity (lbs.)*			Minimum Length (ft.)	Approximate Measurements			
		Vertical	Choker	Basket		Weight (lbs. / ft.)	Body Diameter Relaxed (in.)	Body Width @Load (in.)	Minimum Hardware Diameter (in.)
BSEN30	Purple	2,600	2,100	5,200	1-1/2	.2	5/8	1-1/8	7/16
BSEN60	Green	5,300	4,200	10,600	1-1/2	.3	7/8	1-1/2	5/8
BSEN90	Yellow	8,400	6,700	16,800	3	.4	1-1/8	1-7/8	3/4



TUFLEX WIDE-LIFT

Wide Load Support and Balance

Tuflex wide-lift slings distribute the load over a wide area and offer better balance of larger loads, whether heavy or light.

Features and Benefits

Maintains all the basic *Tuflex* features plus...

Promotes Safety

- Wide body distributes load over wide area and offers improved stability.

Saves Money

- Bearing point of eyes can be shifted to prolong sling life.
- Custom sizes available to fit your needs.

Saves Time

- Standard eye length is 12", making hook-up easy and fast.
- Standard body width is 12", making load balancing easier.

Note:

Wide-lift slings should only be used in basket hitch.

Consult *Lift-All* for special requirements.



Code	Color of Eyes	Vertical Basket Hitch Rated Capacity* (lbs.)
WLEN30	Purple	5,200
WLEN60	Green	10,600
WLEN90	Yellow	16,800
WLEN120	Tan	21,200



Always protect Roundslings from corners, edges, or protrusions. Refer to the Sling Protection section of this catalog to choose the right protection product for your lift.