

WINCH STRAPS & WINCHES

Series 12,000 Load Huggers 3" & 4" Wide Polyester Winch Straps

- Load Hugger Winch Straps are designed for winches on flat bed trucks and trailers.
- Sling protection and corner protectors extend life of Load Huggers.
- Ultimate breaking strength 15,000 lbs.
- Working load limit 5,000 lbs.
- Standard assemblies in 27' or 30' lengths.
- To order a non-standard strap, specify width, length, and end fitting.

Winches must be properly installed with ratchet pawl on top of toothed wheel to help prevent accidental disengagement.

Standard Winch #61222

For 3" & 4" Load Hugger Winch Straps.

7.8-lbs.

Portable Winch #61221

For 3" & 4" Load Hugger Winch Straps.

8.8-lbs.

Winch Bar #61223

For use with both 61221 and 61222 above.

Weight: 4.8-lbs. Diameter: 1-1/4"
Body Length: 31"
Angled Tip Length: 3-1/2"

EZ Winch Handle #61230

For use with both 61221 and 61222 above.

1.2-lbs.

EZ Spool #61231

For use with both 61221 and 61222 above.

2.5-lbs.

* Non-standard lengths available


Web Width (in.)	Length* (ft.)	Standard Part No.	Tuff-Edge® Part No.	Assembly Weight (lbs.)
-----------------	---------------	-------------------	---------------------	------------------------

Flat Hook




4	27	61201	TE61201	5.0
4	30	61202	TE61202	5.4
3	27	61203	TE61203	4.6
3	30	61204	TE61204	5.0

Forged Triangle



4	27	61205	TE61205	5.2
4	30	61206	TE61206	5.6
3	27	61207	TE61207	4.9
3	30	61208	TE61208	5.3

Grab Hook



4	27	61209	TE61209	5.2
4	30	61210	TE61210	5.7
3	27	61211	TE61211	4.9
3	30	61212	TE61212	5.3

Chain Anchor



4	27	61213	TE61213	6.9
4	30	61214	TE61214	7.3
3	27	61215	TE61215	6.6
3	30	61216	TE61216	7.0

7" Sewn Eye



4	27	61217	TE61217	3.3
4	30	61218	TE61218	4.3
3	27	61219	TE61219	4.1
3	30	61220	TE61220	4.0

U-Hook



4	27	61225	TE61225	5.1
4	30	61226	TE61226	5.5
3	27	61227	TE61227	4.8
3	30	61228	TE61228	5.2