

DURA-WEB™ NYLON SLINGS

Best in Abrasion Resistance

Available in two strength classes, all *Dura-Web* slings feature premium abrasive resistant yarns covering all surfaces for extended sling life and long term value.

Features and Benefits

Promotes Safety

- Red core yarn warning system aids in the inspection process.
- Striped webbing helps identify proper capacity.
- *Tuff-Tag*™ provides serial numbered identification for traceability.

Saves Money

- Abrasion resistant fibers cover both faces and edges for greater sling life.
- *Tuff-Tag* provides required OSHA information for the life of the sling.

Saves Time

- Easily identified by stripes.

DURA-WEB 2000	Ply	Part Number	Web Width (in.)	Rated Capacity (lbs.)		
				Vertical	Choker	Basket
	One Ply	UU1202N	2	4,000	3,200	8,000
	Two Ply	UU2202N	2	8,000	6,400	16,000
	One Ply	EE1201NF	1	2,000	1,600	4,000
		EE1202NF	2	4,000	3,200	8,000
	Two Ply	EE2201NF	1	4,000	3,200	8,000
		EE2202NF	2	8,000	6,400	16,000
	One Ply	EN1201N	1	4,000	3,200	8,000
		EN1202N	2	8,000	6,400	16,000
	Two Ply	EN2201N	1	7,800	6,200	15,600
		EN2202N	2	15,200	12,200	30,400

DURA-WEB 2000

- Two black stripes: 2,000 lbs. per inch of width. 25% stronger than other webbing.
- The strongest abrasion resistant sling available.
- *Dura-Web* 2000 slings cannot have tapered eyes.
- *Dura-Web* slings meet or exceed OSHA and ASME B30.9 requirements.
- Available in 1" and 2" widths.

DURA-WEB 1000	Ply	Part Number	Web Width (in.)	Rated Capacity (lbs.)		
				Vertical	Choker	Basket
	One Ply	UU1102N	2	2,000	1,600	4,000
	Two Ply	UU2102N	2	4,000	3,200	8,000
	One Ply	EE1101NF	1	1,000	800	2,000
		EE1102NF	2	2,000	1,600	4,000
	Two Ply	EE2101NF	1	2,000	1,600	4,000
		EE2102NF	2	4,000	3,200	8,000
	One Ply	EN1101N	1	2,000	1,600	4,000
		EN1102N	2	4,000	3,200	8,000
	Two Ply	EN2101N	1	3,900	3,100	7,800
		EN2102N	2	7,600	6,100	15,200

DURA-WEB 1000

- One black stripe: 1,000 lbs. per inch of width.
- The only light-duty web sling with an abrasive resistant surface.
- Wider bearing surface per capacity, helps protect load surface.
- *Dura-Web* slings meet or exceed OSHA and ASME B30.9 requirements.
- Available in 1" and 2" widths.

* **WARNING** Do not exceed rated capacities. Sling tension increases as the angle from horizontal decreases. Slings should not be used at angles of less than 30°. Refer to the Effect of Angle chart in the General Information section of this catalog. **Always protect synthetic slings from being cut by corners and edges. See the Sling Protection section in this catalog.**