

MULTI-PART CABLED SLINGS

Features and Benefits

Maintains all the basic *Lift-All* wire rope sling features plus...



Saves Money

- Good abrasion resistance on 3-Part Cabled Sling increases useful life of sling.
- Resists damage from kinking.

Saves Time

- Flexible and easy to handle.
- Small sleeve over component rope won't get in the way.

3-Part Cabled

Constructed by hand cabling one rope to form a 3-part body with 2-part eyes.



3X7X19



3X6X19

3-Part Cabled

Component Rope Dia. (in.)		Sling Body Dia. (in.)	Rated Capacity* (tons)			Min. Sling Length	Eye Size W X L (in.)		
			Vertical	Choker	Basket		Standard Eye	Crescent Thimble	Slip-Thru Thimble
7X19 GAC	3/16	3/8	1.2	0.82	2.4	2'-0"	3 X 6	2 X 4	2.13 X 4.13
	1/4	1/2	1.9	1.3	3.9	2'-6"	4 X 8	2.25 X 4	2.38 X 4.38
	5/16	5/8	3.0	2.1	6.0	3'-0"	5 X 10	2.75 X 5	3.38 X 6.63
	3/8	3/4	4.3	2.9	8.6	3'-6"	6 X 12	3.25 X 6	3.38 X 6.63
6X19 EIPS IWRC	7/16	7/8	5.8	4.0	12	4'-0"	7 X 14	4.5 X 9	3.75 X 7.13
	1/2	1	7.6	5.2	15	4'-6"	8 X 16	4.5 X 9	3.75 X 7.13
	9/16	1-1/8	9.6	6.6	19	5'-0"	9 X 18	4.88 X 10	4.38 X 8.38
	5/8	1-1/4	12	8.0	23	5'-6"	10 X 20	5.5 X 11	4.38 X 8.38
	3/4	1-1/2	17	11	34	7'-0"	11 X 22	6 X 12	5 X 9.5

Basket ratings based on a minimum D/d of 10 (using sling body dia.). See first page of Wire Rope section.

7-Part Cabled

Constructed by hand cabling one rope to form a 7-part body with 4-part eyes.



7X7X19



7X6X19

7-Part Cabled

Component Rope Dia. (in.)		Sling Body Dia. (in.)	Rated Capacity* (tons)			Min. Sling Length	Eye Size W X L (in.)		
			Vertical	Choker	Basket		Standard Eye	Crescent Thimble	Slip-Thru Thimble
7X19 GAC	1/8	3/8	1.3	0.91	2.6	2'-0"	3 X 6	2 X 4	2.13 X 4.13
	3/16	9/16	2.8	1.9	5.6	2'-6"	4 X 8	2.25 X 6	2.38 X 4.38
	1/4	3/4	4.7	3.2	9.3	3'-0"	5 X 10	2.75 X 7	3.38 X 6.63
	5/16	15/16	6.5	4.5	13	3'-6"	6 X 12	3.25 X 8.50	3.75 X 7.13
	3/8	1-1/8	9.6	6.6	19	4'-0"	7.5 X 15	4.50 X 10	3.75 X 7.13
6X19	7/16	1-5/16	14	9.3	27	4'-6"	9 X 18	4.88 X 13	4.38 X 8.38
	1/2	1-1/2	18	12	35	5'-0"	10 X 20	5.50 X 14.50	4.38 X 8.38

Basket ratings based on a minimum D/d of 10 (using sling body dia.). See first page of Wire Rope section.

* **WARNING** Do not exceed rated capacities. Sling capacity decreases as the angle from horizontal decreases. Slings should not be used at angles of less than 30°. Refer to the Effect of Angle chart in the General Information section of this catalog.

MULTI-PART BRAIDED SLINGS

Features and Benefits

Maintains all the basic *Lift-All* wire rope sling features plus...



Promotes Safety

- Wide bearing surface provides better load control and balance.
- Resists rotation, improving load control.

Saves Money

- 8-Part Round Braid is the most kink-resistant wire rope sling available.
- Reduces load damage.

Saves Time

- Flexible - easy to rig.

6-Part Flat Braid

Constructed by braiding one rope to form a 6-part flat body with web seized eyes.



6-Part Flat Braid										
Component Rope Dia. (in.)	Sling Body Width (in.)	Sling Body Thck. (in.)	Rated Capacity* (tons)			Min. Sling Length	Eye Size W X L (in.)			
			Vertical	Choker	Basket		Standard Eye	Crescent Thimble	Slip-Thru Thimble	
7X19 GAC	1/8	9/16	3/8	0.84	0.74	1.7	2'-0"	3 X 6	2 X 4	2.13 X 4.13
	3/16	13/16	1/2	1.8	1.5	3.5	3'-0"	4 X 8	2.25 X 7.0	2.38 X 4.38
	1/4	1-1/8	11/16	2.9	2.6	5.9	3'-6"	5 X 10	3.25 X 8.5	3.38 X 6.63
	5/16	1-3/8	7/8	4.1	3.6	8.2	4'-6"	6 X 12	4.5 X 11.5	3.38 X 6.63
	3/8	1-11/16	1	6.0	5.3	12	5'-0"	7 X 14	4.88 X 13	3.75 X 7.13
6X19 EIPS IWRC	7/16	2	1-3/16	8.6	7.5	17	6'-0"	8 X 16	6.0 X 16	3.75 X 7.13
	1/2	2-1/4	1-5/16	11	9.8	22	6'-6"	9 X 18	6.0 X 17.5	4.38 X 8.38
	9/16	2-1/2	1-1/2	14	12	28	7'-0"	10 X 20	7.0 X 20	4.38 X 8.38
	5/8	2-13/16	1-11/16	17	15	35	8'-0"	11 X 22	7.0 X 23.5	5.0 X 9.50
	3/4	3-3/8	2	25	22	49	9'-0"	12 X 24	8.5 X 26	6.75 X 11.75

Basket ratings based on a minimum D/d of 10 (using sling body dia.). See first page of Wire Rope section.

8-Part Round Braid

Constructed by braiding one rope to form an 8-part round body with 4-part web seized eyes. 8X7X19 8X6X19

8-Part Round Braid										
Component Rope Dia. (in.)	Sling Body Dia. (in.)	Rated Capacity* (tons)			Min. Sling Length	Eye Size W X L (in.)				
		Vertical	Choker	Basket		Standard Eye	Crescent Thimble	Slip-Thru Thimble		
7X19 GAC	1/8	9/16	1.1	1.0	2.2	2'-0"	3 X 6	2 X 4	2.13 X 4.13	
	3/16	13/16	2.4	2.1	4.7	3'-0"	4 X 8	2.25 X 6	2.38 X 4.38	
	1/4	1-1/8	3.9	3.4	7.8	3'-6"	5 X 10	3.25 X 8	3.38 X 6.63	
	5/16	1-3/8	5.5	4.8	11	4'-6"	6 X 12	4.50 X 10	3.75 X 7.13	
	3/8	1-1/16	8.1	7.1	16	5'-0"	7 X 14	4.63 X 12	3.75 X 7.13	
6X37 EIPS IWRC	7/16*	2	11	10	23	6'-0"	8 X 16	5.50 X 14	4.38 X 8.38	
	1/2	2-1/4	15	13	30	6'-6"	9 X 18	6.0 X 16	5.00 X 9.50	
	9/16	2-1/2	19	16	38	7'-0"	10 X 20	6.50 X 18	5.00 X 9.50	
	5/8	2-13/16	23	20	46	8'-0"	11 X 22	7.0 X 20	6.75 X 11.75	
	3/4	3-3/8	33	29	66	9'-0"	12 X 24	8.0 X 24	8.00 X 14.50	

* 6X19 construction

Basket ratings based on a minimum D/d of 10 (using sling body dia.). See first page of Wire Rope section.

WARNING Do not exceed rated capacities. Sling capacity decreases as the angle from horizontal decreases. Slings should not be used at angles of less than 30°. Refer to the Effect of Angle chart in the General Information section of this catalog.