


REVERSE EYE SLINGS

The Reverse Eye Sling is engineered with reinforcing panels on both sides of the sling. It is the most rugged and versatile of all web slings. The sling incorporates premium wear-resistant material for protection on all surfaces.


The reverse eye sling is not just an endless sling with wear pads.



Single ply endless with reinforced eyes

A. Extended web length makes 2-ply eyes.

B. Reinforcing web piece sewn-on to make 2-ply eyes.



Add wear pads to both sides of body and eyes

C. Single ply endless sling with butted sides.

D. Texturized wear pads on both sides of eyes.

E. Texturized wear pads sewn on both sides of body.



Completed RE sling may be a 1, 2 or 3 ply endless sling with reinforcing webbing for each loop, and texturized wear pad on each side of eyes and sling body.

Features and Benefits

Promotes Safety

- Superior choke hitch grips load security.
- Reinforced eyes improve strength.
- The red core yarn warning system aids in the inspection process.
- *Tuff-Tag*™ provides serial numbered identification for traceability.

Saves Money

- An additional wear-resistant layer offers superior abrasion resistance.
- Reversible eyes reduce wear and increase sling life.
- Heavy-duty slings using *Tuff-Edge*® webbing are armored on all four sides resulting in the toughest web sling available.

Saves Time

- Eyes nest well on crane hook for easy rigging.
- Flat eye construction is available to facilitate removal from under loads.

Heavy-Duty RE Slings: <i>Tuff-Edge</i> III						Sling Width (in.)	Eye Length (in.)	Standard-Duty RE Slings: <i>Webmaster</i> ® Nylon 1200				
Ply	Part Number	Rated Capacity* (lbs.)			Sling THK. (in.)			Part Number	Rated Capacity* (lbs.)			Sling THK. (in.)
		Vertical	Choker	Basket					Vertical	Choker	Basket	
One Ply	RE1802T	4,500	3,600	9,000	5/16	2	9	RE1602N	3,600	2,900	7,200	1/4
	RE1804T	7,700	6,200	15,400	5/16	4	12	RE1604N	6,800	5,400	13,600	1/4
	RE1806T	11,000	8,800	22,000	5/16	6	15	RE1606N	8,000	6,400	16,000	1/4
Two Ply	RE2802T	6,500	5,200	13,000	1/2	2	9	RE2602N	5,200	4,200	10,400	3/8
	RE2804T	13,000	10,400	26,000	1/2	4	12	RE2604N	10,500	8,400	21,000	3/8
	RE2806T	20,000	16,000	40,000	1/2	6	15	RE2606N	14,400	11,500	28,800	3/8
Three Ply	RE3804T	16,400	13,100	32,800	11/16	4	14	RE3604N	14,000	11,200	28,000	1/2
	RE3806T	25,500	20,400	51,000	11/16	6	18	RE3606N	20,000	16,000	40,000	1/2

Reverse Eye Slings using *Webmaster* 1600 webbing are available by special order.

* **WARNING** Do not exceed rated capacities. Sling tension increases as the angle from horizontal decreases. Slings should not be used at angles of less than 30°. Refer to the Effect of Angle chart in the General Information section of this catalog. **Always protect synthetic slings from being cut by corners and edges. See the Sling Protection section in this catalog.**