

TUFF-EDGE® III & WEBMASTER® 1600 SLINGS

EYE/EYE							
Ply	Tuff-Edge III Part No.	Webmaster 1600 Polyester Part No.	Webmaster 1600 Nylon Part No.	Web Width (in.)	Rated Capacity* (lbs.)		
					Vertical	Choker	Basket
One Ply	EE1801TF	EE1801DF	EE1801NF	1	1,600	1,280	3,200
	EE1802TF	EE1802DF	EE1802NF	2	3,200	2,500	6,400
	EE1803TF	EE1803DF	EE1803NF	3	4,800	3,800	9,600
	EE1804TF	EE1804DF	EE1804NF	4	6,400	5,000	12,800
	EE1806TF	EE1806DF	EE1806NF	6	9,600	7,700	19,200
	EE1808TF	EE1808DF	EE1808NF	8	12,800	10,200	25,600
	EE1810TF	EE1810DF	EE1810NF	10	16,000	12,800	32,000
	EE1812TF	EE1812DF	EE1812NF	12	19,200	15,400	38,400
Two Ply	EE2801TF	EE2801DF	EE2801NF	1	3,200	2,500	6,400
	EE2802TF	EE2802DF	EE2802NF	2	6,400	5,000	12,800
	EE2803TF	EE2803DF	EE2803NF	3	8,800	7,040	17,600
	EE2804TF	EE2804DF	EE2804NF	4	11,500	9,200	23,000
	EE2806TF	EE2806DF	EE2806NF	6	16,500	13,200	33,000
	EE2808TF	EE2808DF	EE2808NF	8	19,200	15,400	38,400
	EE2810TF	EE2810DF	EE2810NF	10	22,400	17,900	44,800
	EE2812TF	EE2812DF	EE2812NF	12	26,900	21,500	53,800
Three Ply	EE3801TF	EE3801DF	EE3801NF	1	4,100	3,300	8,200
	EE3802TF	EE3802DF	EE3802NF	2	8,300	6,600	16,600
	EE3803TF	EE3803DF	EE3803NF	3	12,500	10,000	25,000
	EE3804TF	EE3804DF	EE3804NF	4	16,000	12,800	32,000
	EE3806TF	EE3806DF	EE3806NF	6	23,000	18,400	46,000
	EE3808TF	EE3808DF	EE3808NF	8	30,700	24,500	61,400
	EE3810TF	EE3810DF	EE3810NF	10	36,800	29,400	73,600
	EE3812TF	EE3812DF	EE3812NF	12	44,000	35,200	88,000
Four Ply	EE4801TF	EE4801DF	EE4801NF	1	5,000	4,000	10,000
	EE4802TF	EE4802DF	EE4802NF	2	10,000	8,000	20,000
	EE4803TF	EE4803DF	EE4803NF	3	14,900	11,900	29,800
	EE4804TF	EE4804DF	EE4804NF	4	19,800	15,800	39,600
	EE4806TF	EE4806DF	EE4806NF	6	29,800	23,800	59,600
	EE4808TF	EE4808DF	EE4808NF	8	39,700	31,700	79,400
	EE4810TF	EE4810DF	EE4810NF	10	49,600	39,600	99,200
	EE4812TF	EE4812DF	EE4812NF	12	59,500	47,600	119,000



Type 3
Flat Eye
(F)



Type 4
Twisted Eye
(T)

** Replace the F with a T for Twisted Eyes (Type 4).

Eyes on Type 3 and Type 4 slings are tapered at 3" and wider, unless otherwise specified.

EYE LENGTH – APPLIES TO ALL SLINGS

Plies of Web	Sling Width (in.)							
	1	2	3	4	6	8	10	12
1	8.5	10	11	12	16	20	24	24
2	8.5	10	11	12	16	20	24	24
3	10.0	12	14	16	18	24	24	24
4	10.0	12	14	16	18	24	24	24

* **WARNING** Do not exceed rated capacities. Sling tension increases as the angle from horizontal decreases. Slings should not be used at angles of less than 30°. Refer to the Effect of Angle chart in the General Information section of this catalog. **Always protect synthetic slings from being cut by corners and edges. See the Sling Protection section in this catalog.**

TUFF-EDGE® III & WEBMASTER® 1600 SLINGS

General Information
Web Slings
Round Slings
Sling Protection
Wire Rope
Chain Slings
Rigging Hardware
Mesh Slings
Cargo Control
Lift-All Hoists
Hoist Rings
Plate Clamps
Lifting Devices

ENDLESS							
Ply	Tuff-Edge III Part No.	Webmaster 1600 Polyester Part No.	Webmaster 1600 Nylon Part No.	Web Width (in.)	Rated Capacity* (lbs.)		
					Vertical	Choker	Basket
One Ply	EN1801T	EN1801D	EN1801N	1	3,200	2,500	6,400
	EN1802T	EN1802D	EN1802N	2	6,400	5,000	12,800
	EN1803T	EN1803D	EN1803N	3	8,800	7,040	17,600
	EN1804T	EN1804D	EN1804N	4	11,500	9,200	23,000
	EN1806T	EN1806D	EN1806N	6	16,500	13,200	33,000
	EN1808T	EN1808D	EN1808N	8	19,200	15,400	38,400
	EN1810T	EN1810D	EN1810N	10	22,400	17,900	44,800
	EN1812T	EN1812D	EN1812N	12	26,900	21,500	53,800
Two Ply	EN2801T	EN2801D	EN2801N	1	6,200	4,900	12,400
	EN2802T	EN2802D	EN2802N	2	12,400	9,900	24,800
	EN2803T	EN2803D	EN2803N	3	16,300	13,000	32,600
	EN2804T	EN2804D	EN2804N	4	20,700	16,500	41,400
	EN2806T	EN2806D	EN2806N	6	30,500	24,400	61,000
	EN2808T	EN2808D	EN2808N	8	40,000	32,000	80,000
	EN2810T	EN2810D	EN2810N	10	47,000	37,600	94,000
	EN2812T	EN2812D	EN2812N	12	56,000	44,800	112,000
Three Ply	EN3801T	EN3801D	EN3801N	1	8,000	6,400	16,000
	EN3802T	EN3802D	EN3802N	2	16,000	12,800	32,000
	EN3803T	EN3803D	EN3803N	3	21,500	17,200	43,000
	EN3804T	EN3804D	EN3804N	4	28,700	23,000	57,400
	EN3806T	EN3806D	EN3806N	6	40,700	32,500	81,400
	EN3808T	EN3808D	EN3808N	8	46,000	36,800	92,000
	EN3810T	EN3810D	EN3810N	10	51,500	41,200	103,000
	EN3812T	EN3812D	EN3812N	12	59,200	47,300	118,400
Four Ply	EN4801T	EN4801D	EN4801N	1	10,000	8,000	20,000
	EN4802T	EN4802D	EN4802N	2	19,800	15,800	39,600
	EN4803T	EN4803D	EN4803N	3	26,700	21,300	53,400
	EN4804T	EN4804D	EN4804N	4	35,600	28,400	71,200
	EN4806T	EN4806D	EN4806N	6	50,500	40,400	101,000
	EN4808T	EN4808D	EN4808N	8	57,600	46,000	115,200
	EN4810T	EN4810D	EN4810N	10	67,200	53,700	134,400
	EN4812T	EN4812D	EN4812N	12	80,700	64,500	161,400

Note: Type 5 (Endless) slings are not tapered unless specified.



Scan and learn more about Lift-All's Tuff-Edge III.

Tuflex® is an alternative...

For 3-ply and 4-ply slings wider than 6", Tuflex Roundslings should be seriously considered. Tuflex offers increased flexibility, ease of use and lower cost.

* **WARNING** Do not exceed rated capacities. Sling tension increases as the angle from horizontal decreases. Slings should not be used at angles of less than 30°. Refer to the Effect of Angle chart in the General Information section of this catalog. Always protect synthetic slings from being cut by corners and edges. See the Sling Protection section in this catalog.

TUFF-EDGE® & WEBMASTER® 1600 SLINGS



TYPE U - UNILINK™ HARDWARE SLINGS

Ply	Tuff-Edge III Part No.	Web Width (in.)	Rated Capacity* (lbs.)			Webmaster 1600 Polyester Part No.***	Webmaster 1600 Nylon Part No.***
			Vertical	Choker	Basket		
One Ply	UU1802T	2	3,200	2,500	6,400	UU1802D	UU1802N
	UU1803T	3	4,800	3,800	9,600	UU1803D	UU1803N
	UU1804T	4	6,400	5,000	12,800	UU1804D	UU1804N
Two Ply	UU2802T	2	6,400	5,000	12,800	UU2802D	UU2802N
	UU2803T	3	8,800	7,040	17,600	UU2803D	UU2803N
	UU2804T	4	11,500	9,200	23,000	UU2804D	UU2804N

Note: Unilink is the standard fitting for widths 2"-4" triangle and chokers available on special order only.



Type 1 (TC)



Type 2 (TT)



Type 1 (TC)



Type 2 (TT)

TYPE 1 (TC) & TYPE 2 (TT) WEB-TRAP™ HARDWARE SLINGS

Ply	Tuff-Edge III Part No.***		Web Width (in.)	Rated Capacity* (lbs.)			Webmaster 1600 Polyester Part No.***		Webmaster 1600 Nylon Part No.***	
	Type 1	Type 2**		Vertical	Choker	Basket	Type 1	Type 2**	Type 1	Type 2**
One Ply	TC1806T	TT1806T	6	9,600	7,700	19,200	TC1806D	TT1806D	TC1806N	TT1806N
	TC1808T	TT1808T	8	12,800	10,200	25,600	TC1808D	TT1808D	TC1808N	TT1808N
	TC1810T	TT1810T	10	16,000	12,800	32,000	TC1810D	TT1810D	TC1810N	TT1810N
	TC1812T	TT1812T	12	19,200	15,400	38,400	TC1812D	TT1812D	TC1812N	TT1812N
	TC1816T	TT1816T	16	25,500	20,400	51,000	TC1816D	TT1816D	TC1816N	TT1816N
Two Ply	TC2806T	TT2806T	6	16,800	13,400	33,600	TC2806D	TT2806D	TC2806N	TT2806N
	TC2808T	TT2808T	8	22,400	17,900	44,800	TC2808D	TT2808D	TC2808N	TT2808N
	TC2810T	TT2810T	10	28,000	22,400	56,000	TC2810D	TT2810D	TC2810N	TT2810N
	TC2812T	TT2812T	12	33,600	26,800	67,200	TC2812D	TT2812D	TC2812N	TT2812N
	TC2816T	TT2816T	16	44,800	35,800	89,600	TC2816D	TT2816D	TC2816N	TT2816N

** Type 2 (TT) cannot be used in a choker hitch.

*** To order aluminum hardware, single ply 2" - 6" only, add A after TC or TT.

Custom configurations available.

* **WARNING** Do not exceed rated capacities. Sling tension increases as the angle from horizontal decreases. Slings should not be used at angles of less than 30°. Refer to the Effect of Angle chart in the General Information section of this catalog. Always protect synthetic slings from being cut by corners and edges. See the Sling Protection section in this catalog.