


## TUFLEX® VEHICLE RECOVERY STRAPS THE HEAVY DUTY RECOVERY STRAPS!

*Tuflex* straps elongate to 3% and are designed to prevent dangerous recoil.



Our *Tuflex* version of the *Tow-All*™ strap offers the most rugged synthetic strap on the market. We start with our standard *Tuflex* Roundsling:

- 1** Add an additional jacket of texturized, abrasion resistant nylon, installed over the body, creating an eye/eye style.
- 2** The 18" long eyes are then covered with ballistic nylon material for additional protection.
- 3** An 18" long sliding sleeve wear pad provides added protection against load edges.

### Inspection Criteria for all *Tow-All* Vehicle Recovery straps:

Remove from service if any of the following are visible:

- Signs of melting, charring or chemical damage.
- Holes, tears, snags, or cuts on the face or edge of webbing.
- Visible signs of damage exposing core yarns.
- Signs of excessive abrasive wear.
- Broken or worn threads in the stitch patterns.
- Any other visible damage.
- Illegible or missing identification tag.
- Knots.

| Part Number                | Ultimate Breaking Strength* (lbs.) | Towing Capacity+ (lbs.) |
|----------------------------|------------------------------------|-------------------------|
| TSEN90X20<br>TSEN90X30     | 42,000                             | 14,000                  |
| TSEN120X20<br>TSEN120X30   | 52,500                             | 17,500                  |
| TSEN150X20<br>TSEN150X30   | 66,000                             | 22,000                  |
| TSEN180X20<br>TSEN180X30   | 84,000                             | 28,000                  |
| TSEN240X20<br>TSEN240X30   | 105,900                            | 35,300                  |
| TSEN360X20<br>TSEN360X30   | 154,800                            | 51,600                  |
| TSEN600X20<br>TSEN600X30   | 264,900                            | 88,300                  |
| TSEN800X20<br>TSEN800X30   | 330,000                            | 110,000                 |
| TSEN1000X20<br>TSEN1000X30 | 450,000                            | 150,000                 |

\* Ultimate breaking strength when new.  
+ Do not exceed towing capacity.  
Above ratings reflect a 3:1 design factor.

To use product for lifting applications with a 5:1 design factor, contact *Lift-All* when ordering.

Refer to photographs of damaged *Tuflex* roundslings in the Roundslings section of this catalog.