

Features and Benefits

- Backup Attachment Points in Each
 Eye A secondary yellow attachment
 loop in each eye allows for attachment of
 back-up lanyards to improve safety should
 an unplanned release of the sling occur
 during a recovery operation. Its use is
 recommended whenever any uncertainty
 exists about the amount of loading or the
 integrity of the attachment points.
- Strength & Toughness Made from high tenacity Tuff-Edge® III polyester to provide the strength and dynamics needed for towing and recovery operations.
- SPUL Towing A higher Straight-Line Pulling Unrestricted on Level Surface (SPUL) Towing Rating is also provided.
- When used in a vertical or choker hitch the 1-ply ResQ-All strap is great for use with soft shackles at the strap's full rated capacity.
- Each eye has a Cordura-lined bearing point for longer sling life.
- Standard length (ft.): 16, 20, 26, 30.

Ply	Part Number	Strap Width (in.)	Rated Capacity (lbs.)			
			Towing* @ 3:1	Lifting & Recovery @ 5:1		
				Vertical	Choker	Basket**
1 Ply	RS1802TG	2	5,300	3,200	2,500	6,400
	RS1803TG	3	8,000	4,800	3,800	9,600
	RS1804TG	4	10,600	6,400	5,000	12,800
	RS1806TG	6	16,000	9,600	7,700	19,200
2 Ply**	RS2802TG	2	10,600	6,400	5,000	12,800
	RS2803TG	3	14,600	8,800	7,040	17,600
	RS2804TG	4	19,100	11,500	9,200	23,000
	RS2806TG	6	27,500	16,500	13,200	33,000
	RS2808TG	8	32,000	19,200	15,400	38,400
	RS2810TG	10	36,600	22,400	17,900	44,800
	RS2812TG	12	44,800	26,900	21,500	53,800

^{*} SPUL Towing - A higher Straight-Line Pulling Unrestricted on Level Surface (SPUL) Towing Rating.

^{**}When using a 2-ply strap or basket hitch a 50% rating reduction factor should be applied whenever using soft shackles.